



 *Masonite*<sup>®</sup>

ARTEK™ NON-TEXTURED FIBERGLASS DOOR COLLECTION



Non-Textured Fiberglass Entry Doors



**High-Performance Fiberglass Facings**

Specially engineered fiberglass door facings provide maximum protection and durability. ArTek™ will not dent and resists splitting, cracking and warping. ArTek also replicates the appearance of a wood door with stile and rail detail while providing an extra smooth surface for finishing.

**Specialty™ Glass Inserts**

All Specialty™ decorative glass inserts feature a triple-pane 1" insulated assembly providing maximum design selection and performance. Double-pane insulated glass inserts and flush-glazed frame designs are also available.

**Internal Blocking**

Lock area is reinforced with a 21" lock block to provide a solid mounting surface for decorative hardware

**Polyurethane Core**

Rigid polyurethane foam, meeting strict environmental guidelines, provides maximum thermal protection and dimensional stability.

**Engineered Stiles**

Hinge and lock stiles feature laminated lumber providing excellent dimensional stability

**Rot-Resistant Bottom Rail**

A high-performance, composite material is utilized on all ArTek bottom rails, giving excellent rot-resistance.



**True Square-Edge Design**

The square-edge design of ArTek offers an attractive wood door appearance and permits easy field machining.

**High-Definition Panel Profile**

ArTek features a high-definition, patented panel profile providing excellent shadow lines and distinct panel designs.

NOTE: Glass lites shown are Masonite's Specialty™ Glass



Top Left: ArTek with Seville glass, Door: ATK-105-841, Sidelites: ATKSL-200-841  
 Bottom Left: ArTek with Marquise glass, Door: ATK-404-778, Sidelites: ATKSL-450-778, Transom: C-646  
 Center: ArTek with Seville glass, Door: ATK-106-841

Top Right: ArTek with Madrid glass, Door: ATK-106-900, Sidelites: ATKSL-129-900  
 Bottom Right: ArTek with Nassau glass, Door: ATK-404-871, Sidelites: ATKSL-450-871, Transom: C-871

Width x Height	FLUSH	BLANK TOP 4-PANEL	NEW ENGLAND 4-PANEL	6-PANEL	FLUSH SIDELITE	1-PANEL SIDELITE
2'0" x 6'8"	■ 🔥					
2'0" x 7'0"	■ 🔥					
2'0" x 8'0"	■					
2'6" x 6'8"	■ 🔥					
2'6" x 7'0"	■ 🔥					
2'6" x 8'0"	■					
2'8" x 6'8"	■ 🔥	■		■ 🔥		
2'8" x 7'0"	■ 🔥			■ 🔥		
2'8" x 8'0"	■			■		
2'10" x 6'8"	■ 🔥	■		■ 🔥		
2'10" x 7'0"	■ 🔥			■ 🔥		
2'10" x 8'0"	■			■		
3'0" x 6'8"	■ 🔥	■		■ 🔥		
3'0" x 7'0"	■ 🔥			■ 🔥		
3'0" x 8'0"	■			■		
1'0" x 6'8"					■ ○	■ ○
1'0" x 7'0"					■ ○	■ ○
1'0" x 8'0"					■ ○	■ ○
1'2" x 6'8"					■	■
1'2" x 7'0"					■	■
1'2" x 8'0"					■	■

Notes: ○ 10" x 6'8", 7'0" or 8'0" sidelite available

🔥 Available as 20-minute Warnock Hersey® listed fire doors (fire doors feature an engineered solid core)

- Positive Pressure per UBC 7-2 (1997) and UL 10(c)
- Neutral Pressure per UBC 7-2 (1994) and UL 10(b)
- Intumescent edge-seal required for Positive Pressure
- Rated for single openings up to 3'0" x 7'0"

# ArTek™ Flush-Glazed Doors



## Richness and Significance

Adding richness and significance to a home's exterior is the PREMVU® ArTek™ advantage. The non-textured, incredibly smooth, fiberglass surface and variety of flush-glazed options enhance the value of any home.

### Special Features:

- **Superior aesthetics**  
The flush-glazed feature of PREMVU provides a much cleaner appearance than the traditional glass insert. The glazing bead is flush with the surface of the door and does not have unsightly screw holes.
- **Engineered durability**  
PREMVU ArTek Flush-Glazed Door Panels incorporate cutting-edge fiberglass technology into an exceptionally dent-proof and weather-resistant door.
- **Wider viewing area**  
PREMVU brightens up any room with 20% more viewing area – standard and wide glass inserts are available.
- **Durable and energy efficient**  
All PREMVU ArTek Flush-Glazed Door Panels are manufactured with fiberglass facings and polyurethane foam cores – maximizing strength, durability and energy efficiency.

### Factory Glazed Options:



1-lite Clear and  
1-lite High-Performance Clear  
Insulated Glass  
6'8" or 8'0"



1-lite  
Internal Mini-Blind\*  
6'8"



15-lite  
White Internal Grille  
6'8"



18-lite  
White Internal Grille  
8'0"



## PREMVU® Series ArTek™ Flush-Glazed Doors:

	Door Panel (width x height)							
Glass Widths	2'6"x6'8"	2'6"x8'0"	2'8"x6'8"	2'8"x8'0"	2'10"x6'8"	2'10"x8'0"	3'0"x6'8"	3'0"x8'0"
20"	■	■	■	■				
22"			■	■	■	■	■	■
26"							■*	■*

Notes: \*Internal mini-blinds are NOT available in a 26" glass width.  
PREMVU Door Panels are also available "open" (no glass) with stops available for 1" insulated glass insert.



Masonite International Corporation

**Blackstock Lumber Co., Inc.**

**1039 Elliott Avenue West • Seattle, WA 98119**

**Phone (206) 284-1313 • Fax (206) 281-0062**

**www.blackstocklumber.com**

Masonite and PREMVU are registered trademarks of Masonite International Corporation. ArTek and Specialty are trademarks of Masonite International Corporation. Warnock Hersey is a registered trademark of Intertek Testing Services.

Our continuing program of product improvement makes specification, design and product detail subject to change without notice.